

1.5/1.8/2 ton electric pallet truck (lithium battery)



FEATURES

- The whole vehicle is simple, dexterous, reliable and easy to operate.
- Wide open design, easy to remove and replace the battery
- The design of operating handle, electric lifting function
- The sturdy metal cover protects the motor and wheels

1.5-2T

ELECTRIC PALLET TRUCK
LITHIUM BATTERY

Characteristics	1.1	Manufacturer	Unit	JAC					
	1.2	Model		CBD15				CBD20	
	1.3	Power unit		electric				electric	
	1.4	Operation		Walkie				Walkie	
	1.5	Rated traction weight	kg	1500				2000	
	1.6	Load centre	mm	600				600	
	1.7	Axle centre to fork face	mm	944				944	
	1.8	Wheel base	mm	1243				1243	
Weights	2.1	Service weight with battery	kg	156				146	
Wheels/Tyres	3.1	Wheels type		PU				PU	
	3.2	Driving wheel size	Φ×	Φ210×70				Φ210×70	
	3.3	Bearing wheel size	Φ×	Φ80×60				Φ80×60	
	3.4	Wheels, number front/rear (x = driven)		1x/4				1x/4	
	3.5	Track width	mm	390/535				400/535	
Dimensions	4.1	Lift	mm	200				200	
	4.2	Overall height (With handle)	mm	610/1212				740/1160	
	4.3	Lowered hength	mm	85				85	
	4.4	Overall length	mm	1615				1603	
	4.5	Length to fork face	mm	465				453	
	4.6	Overall width	mm	550/685				550/685	
	4.7	Fork dimensions	s/e/l	50/150/1150				50/150/1150	
	4.8	Width of forks	mm	550/685				550/685	
	4.9	Min.Ground clearance	mm	35				35	
	4.10	Aisle width with pallet 1000 x 1200 across	mm	1815				1804	
	4.11	Aisle width with pallet 800 x 1200 along	mm	1865				1854	
	4.12	Min.Turning radius	mm	1405				1398	
Performance	5.1	Travel speed,laden/unladen	km/h	4.2/4.5				4.2/4.5	
	5.2	Lifting speed,laden/unladen	mm/s	40/62				40/62	
	5.3	Maximum climbing ability, with/without	%	5/8				5/10	
	5.4	Service brake		electromagnetic braking				electromagnetic braking	
Drive/Battery	6.1	Drive motor, 60 minute rating	kW	0.75				0.75	
	6.2	Lift motor rating at S3 15%	kW	0.8				0.8	
	6.3	Battery voltage/rated capacity (lithium	V/Ah	24/20	24/30	24/40	24/60	48/20	48/30
	6.4	Battery weight (± 5%)	kg	6	7.8	10.2	13.2	10.2	13.2
Others	7.1	Type of drive control		DC power				DC power	
	7.2	Noise level at operator's ear	dB(A)	≤70				≤70	
	7.3	Steering type		Mechanical steering				Mechanical steering	